



Light-emitting diode module Teleline T2 2,0W



DESIGNED FOR
BACKLIGHT LIGHTBOXES



BEST FOR 70-100MM
DEEP LIGHTBOXES




RECOMMENDED DEPTH:
C-C DISTANCE RATIO



HIGH POWER FOR
EXTRA BRIGHTNESS



IP67
DUST AND WATER
PROTECTED



200lm
HIGH BRIGHTNESS
200 LM PER MODULE



6500 K
6500 K
AND OTHER COLORS



5 YEAR EXTENDED
WARRANTY

TECHNICAL INFORMATION

| | |
|---------------------------|--------------|
| LED type | 3030 |
| Input | 12V DC |
| Color temperature | 6500 K |
| Beam angle | 175° |
| Protection level | IP 67 |
| Center-to-center distance | 350 mm |
| Working temperature | -30°C + 50°C |
| Available colors | ● |
| Power | 2 W |
| Light output | 200 lm |


ILLUMINATION TABLE

| Installation depth | Distance between centers | Quantity per 1 sq.m. | Power per 1 sq.m. |
|--------------------|--------------------------|----------------------|-------------------|
| 70 mm | 180 mm | 36 pcs | 43,2 W |
| 80 mm | 200 mm | 25 pcs | 30 W |
| 90 mm | 230 mm | 25 pcs | 30 W |
| 100 mm | 250 mm | 16 pcs | 19,2 W |



LIGHT DISTRIBUTION GRAPH


Beam angle is 175°



DIMENSIONS



CONNECTION



PACKAGING

| Packing type | Chain | Package | Box |
|--------------|--------|---------|----------|
| Quantity | 20 pcs | 100 pcs | 1600 pcs |
| Weight | 0,3 kg | 1,5 kg | 25,2 kg |